

Network Camera

Guardian Watch

SERIES

**5MP 36X Zoom WDR Network
Outdoor IR PTZ Camera**

The Guardian Watch Series PTZ cameras offer a 360-degree surveillance solution with advanced zoom, high-resolution imaging, and superior night vision capabilities. Designed for both indoor and outdoor use, these weather-resistant cameras feature smart motion tracking, remote access, and seamless integration with existing security systems. Experience reliable and user-friendly monitoring with tamper detection and a professional interface for heightened security and peace of mind.

MODEL NO: TS-CINPZ-5MM51I661



Main Features

- 5MP High Resolution, PALNTSC, ONVIF support.
- Professional IP Pan/Tilt/Zoom speed dome, simple setup, IR-Cut 450ft night vision.
- 1/2.8" CMOS Sensor, Wide Angle 2.8mm-12mm, 36X Optical Zoom, IP66 Outdoor Waterproof, Anti-Corrosion Polymer Shell: great for salty ocean-front.
- PTZ Speed : 90 degrees Vertical, 360 degree Endless horizontal.
- Focus Length 5-90mm.
- Support P2P real-time message push



Key Features

✓ AI Video Analytics

- 8 intelligent VCA modes powered by AI engine, which can intelligently filter objects to focus on human and vehicle detection.
- People Counting technology provides high accuracy and real-time data Based on AI algorithm with statistic reports.
- Face Detection function detects human faces in the monitoring scene and captures the snapshots, which greatly enhances the monitoring efficiency.



✓ Intelligent PTZ Auto Tracking

With AI detection, Milesight Network Camera could leverage motor mechanism to perform Pan/Tilt/Zoom to track the moving human or vehicle automatically and adjust zoom status flexibly according to the target distance with the powerful optical zoom capability.



✓ Up to 42X Optical Zoom

Embedded with optical zoom lens, the cameras' resolution is up to 42X optical Zoom which allows the user to zoom up to distant objects while still Maintaining the clarity and delivering high quality video over the entire zoom Range.



✓ 30fps@4K

Providing 4K HD resolution with frame rate of 30fps, the camera performs well in catching detailed image regardless of the moving speed.





Specifications

Camera	
Model No	TS-CINPZ-5MM511661
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.009 Lux @ F1.55, B/W: 0 Lux with IR on
Lens	4.7~141mm
WDR	120dB Super WDR
Shutter Time	1/100000s~1s
Digital Zoom	16X
Day/Night Mode	Day/Night/Auto/Customize/Schedule
S/N	>55dB
Focal Length	5.7~205.2mm, 36X Optical Zoom
Zoom Speed	Approx 7s (Wide-Tele)
Field of View	H65°~H2.5°/D72°~D2.9°/V40°~V1.4°
Focus Control	Auto/Semi-Auto/Manual
Minimum Working Distance	11500/1500mm (Wide/Tele)
Aperture	F1.55~F4.8
Iris Control	Auto
PTZ	
Pan Range/Pan Speed	360° endless/Pan Manual Speed: 0.1°~250°/s, Pan Preset Speed: 250°/s
Tilt Range/Tilt Speed	-5°~90° (Auto Flip)/Tilt Manual Speed: 0.1°~160°/s, Tilt Preset Speed: 160°/s
Proportional Zoom	Support
Patrol	8 Patrols, up to 48 preset each patrol
Pattern	4 Patterns
Auto Tracking	Support
Power Off Memory	Support
Other Function	Auto Scan, Auto Home, Preset Freezing, 3D Positioning, PTZ Limits, Initial Position
Audio & Video Encoding	
IR Distance	Up to 300m
IR Angle	Auto/Manual
VIDEO	
Max. Image Resolution	3840x2160 60Hz: 30fps @ (3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576)
Primary Stream	60Hz: 30fps @ (3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576)
Secondary Stream	60Hz: 30fps @ (704x576, 640x480, 640x360, 352x288, 320x240) 50Hz: 25fps @ (704x576, 640x480, 640x360, 352x288, 320x240)





Specifications

Tertiary Stream	60Hz:30fps@(1920x1080,1280x720,704x576,640x480,640x360,320x240) 50Hz:25fps@(1920x1080,1280x720,704x576,640x480,640x360,320x240)
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Privacy Masking	Upto8Areas(MaskAreaandMosaicAreaareoptional)
Video Bitrate	16Kbps~16Mbps(CBR/VBRAdjustable)
ROI	Upto8areas
Image Setting	Brightness/Contrast/Saturation/Sharpness Interface
Interface	
Ethernet	1*RJ4510M/100MEthernetPort
Audio I/O	1/1
Alarm I/O	4/2
RS485	Support
Audio	
Audio Compression	G.711/AAC/G.722/G.726
AudioSamplingRate	8/16/32/44.1/48KHz
Audio Bitrate	16~256kbps Two-way Audio Support
Intelligent Analytics	
Video Analysis	RegionEntrance,RegionExiting,AdvancedMotionDetection,TamperDetection, LineCrossing,Loitering,ObjectLeft,ObjectRemoved
FaceDetection&Face Attribute Recognition	Detectandcapturefaces, getreal-timesnapshots.TheattributesincludeAge, Gender, Glasses, MaskandCap.
PeopleCounting&Report	Countthenumberofpeopleenteringorexiting, upto4detectionareasforregionalpeoplecounting
System	
Advanced Function	BLC,HLC,2DDNR,3DDNR,Defog,AWB, IPAddressFiltering,AGC,Anti-flicker,CorridorMode,Deblur,Watermark
Event Trigger	MotionDetection,NetworkDisconnection,ExternalInput,AudioAlarm,etc.
Event Action	FTPUpload,SMTPUpload,SDCardRecord,ExternalOutput,SIPPhone,PTZMotion,HTTPNotification,etc.
System Compatibility	ONVIFProfileG&Q&S&T,API
Approval	
EMC	FCC (FCC/23M02012); CE
Safety	UL/23M02014; BIS IS 13252(PART 1):2010/ IEC 60950-1 : 2005 : IP67
Environment	CE-ROHS
Ingress Protection	Weather Proof IP66;IK10
General	
Working Condition	Temperature:-40°C~60°C/Humidity:0~95%(Non-condensing)
Power Supply	PoE(802.3at)/AC24V/3A±10%
Power Consumption	13WMAX/ 28WMAX(WithIRon)
Warranty	2Years/3Years(Optional)

